


TRAVI INP



Profilo	Dimensioni					Modulo di resistenza a flessione W_x [cm ³]
	Peso [kg/m]	Sezione [cm ²]	h [mm]	b [mm]	a [mm]	e [mm]
INP 80	5,9	7,57	80	42	3,9	5,9
100	8,3	10,6	100	50	4,5	6,8
120	11,1	14,2	120	58	5,1	7,7
140	14,3	18,2	140	66	5,7	8,6
160	17,9	22,8	160	74	6,3	9,5
180	21,9	27,9	180	82	6,9	10,4
200	26,2	33,4	200	90	7,5	11,3
220	31	39,5	220	98	8,1	12,2
240	36,2	46,1	240	106	8,7	13,1
260	41,9	53,3	260	113	9,4	14,1
280	47,9	61	280	119	10,1	15,2
300	54,2	69	300	125	10,8	16,2
320	61	77,7	320	131	11,5	17,3
360	76,1	97	360	143	13	19,5
400	92,5	118	400	155	14,4	21,6
450	115	147	450	170	16,2	24,3
500	141	179	500	185	18	27
600	199	254	600	215	21,6	32,4

Profilo	Distanza tra gli appoggi [m]										
	2	3	4	5	6	7	8	9	10	11	12
INP											
80	1230	810	597	467	378	-	-	-	-	-	-
100	2166	1430	1058	831	678	565	-	-	-	-	-
120	3466	2292	1700	1340	1096	919	783	-	-	-	-
140	5207	3447	2560	2023	1659	1396	1194	1035	904	-	-
160	7452	4938	3672	2906	2389	2014	1729	1503	1319	1165	-
180	10260	6804	5064	4012	3303	2791	2401	2093	1842	1633	1455
200	13644	9052	6743	5347	4408	3730	3214	2808	2477	2202	1968
220	17730	11768	8772	6962	5745	4866	4200	3675	3248	2894	2593
240	22520	14953	11151	8856	7313	6201	5358	4695	4156	3709	3331
270	28140	18690	13944	11080	9157	7771	6721	5895	5226	4671	4201
300	34528	22939	17120	13610	11254	9557	8273	7263	6446	5768	5196
330	41620	27656	20647	16420	13584	11543	9998	8785	7804	6991	6304
360	49862	33140	24748	19689	16295	13854	12008	10559	9387	8417	7599
400	69416	46150	34480	27447	22733	19344	16783	14775	13153	11812	10681
450	93319	62059	46382	36939	30613	26068	22636	19946	17776	15983	14474
500	130010	86482	64660	51521	42723	36406	31640	27907	24898	22415	20327
550	175462	116740	87308	69593	57735	49226	42808	37785	33739	30402	27599
600	295666	196779	147236	117431	97494	83197	72424	64001	57223	51641	46956

Carico in Kg uniformemente distribuito per acciaio con carico di sicurezza $K = 16 \text{ kg/mm}^2$



POLETTI SPA

POLETTI SPA